





## PACKAGE DIMENSION

TY-571WH5TM55-2600



### Selection Guide

Part No.	Dice		Lens Color	(If=20mA)	Viewing Angle
	Raw Material	Emitted Color		TYP. (Mcd)	
TY-571WH5TM55-2600	InGaN	White	Tiny Milky	2600	55°

### Absolute Maximum Ratings at TA=25°C

Parameter	Symbol	Maximum Rating	Units
Power Dissipation	PD	100	mW
Peak Forward Current <sup>4</sup>	IFP	100	mA
Forward Current	IF	25	mA
Reverse Voltage	VR	5	V
Capacitance	C	20	pF
Operating/Storage Temperature	TA/TSTG	-40°C to +85°C	
Lead Solder Temperature	TSOL	260°C for 5 Seconds	

### Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	TYP.	MAX.	Units	Test Condition
Chromaticity Coordinates	x	0.31	-	nm	IF=20mA
	y	0.32	-	nm	IF=20mA
Spectral Line Half-width	Δλ	20	-	nm	IF=20mA
Forward Voltage	VF	3.50	4.00	V	IF=20mA
Reverse Current	IR	-	100	uA	VR=5V

Notes:

1. All dimension are in millimeter (inches);
2. Tolerance is ±0.25mm(0.01") unless otherwise specified;
3. Not recommend to solder within 3mm from the resin;
4. 1/10 Duty Cycle, 0.1ms Pulse Width.